Philips
Composite A/V to scart cable

3.0 m

SWV3530

Turn up your viewing experience

with this composite A/V to scart cable

Step up to a better connection for transferring audio/video signals between your components.

Enjoy better picture quality
- 24 carat gold-plated connectors optimize signal

Enjoy better audio quality
- High purity copper conductor for reliable signal transfer
- 24 carat gold-plated connectors optimize signal

Protects against signal loss
- Copper braided reinforced aluminum shielding

Easy installation
- Color coded connectors for instant recognition
- Plug and play for easy use

Enjoy extended durability
- Protective metal shell for extended durability
- Flexible PVC jacket
- Rubber strain relief

PHILIPS
sense and simplicity

Composite A/V to scart cable
3.0 m

SWV3530/10

Specifications

Outer Carton
- EAN/UPC/GTIN: 87 10895 93407 7
- Quantity: 36
- Gross weight: 12.74 kg
- Tare weight: .50 kg
- Net weight: 12.24 kg
- Length: 590 mm
- Width: 360 mm
- Height: 300 mm

Dimensions
- Gross weight: .34 kg
- Tare weight: .06 kg
- Net weight: .28 kg
- Product length: 28 cm
- Product dimensions (W x H): 175 x 30 mm

Product highlights

24 carat gold-plated connector
24 carat gold-plated connectors ensure the best signal quality for your components.

High purity copper
This copper conductor provides high accuracy in signal transfer with minimal resistance.

24 carat gold-plated connector
24 carat gold-plated connectors ensure the best signal quality for your components.

Braided shielding
Copper braided reinforced aluminum shielding protects against signal loss and interference.

Color-coded connectors
Color coded connections make it easy to install your cable into the correct inputs and outputs

Plug and play
Plug and play offers easy installation of components without time-consuming installations.

Metal shell
The metal shell protects the internal connection of the cable. It ensures durability and the reliability of your connection.

Flexible PVC Jacket
Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.

Rubber strain relief
Rubber strain relief provides a secure, yet flexible juncture between the cable and the plug.

Issue date 2008-03-29
Version: 3.1.7
12 NC: 9082 100 06287
EAN: 87 10895 93406 0

© 2008 Koninklijke Philips Electronics N.V.
All Rights reserved.
Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com